



Series 211 Stinger™ Convection Vacuum Gauge Module Measurement Unit & Display - Torr/mTorr

- **Wide measurement range**
1.0 x 10⁻⁴ to 1000 Torr
1.3 x 10⁻⁴ to 1333 mbar

Monitor your vacuum system from atmosphere to 10⁻⁴ Torr with a single gauge.

- **Built-in digital display with analog output and setpoint relay.**

Easy setup and operation.

- **Wider measuring range and better accuracy than TC gauges.**

Upgrade your vacuum system and process performance.

- **Also a low cost, plug-compatible direct drop-in replacement for the most basic Granville-Phillips[®] Mini-Convectron[®] models.**

*Significant cost savings
Simplest and lowest cost vacuum gauge solution for many vacuum systems.*



CVM211 Sensor

The sensor inside the CVM211 *Stinger*[™] module incorporates numerous design enhancements compared to other traditional convection vacuum gauges.

Temperature compensation has been moved out of the vacuum environment and placed around the outside of the vacuum gauge tube. This has eliminated a dozen or so unnecessary parts and welds, significantly increasing the reliability, providing optimal vacuum measurement while reducing cost. The improved mechanical strength results in a highly robust vacuum gauge less susceptible to mechanical shock and vibration.

Other design features include reduced internal volume and significant reduction of internal surface area resulting in faster pump-down and less outgassing. A fine mesh screen in the gauge inlet port helps prevent particulate contamination from entering the gauge. The gauge is shielded against RF interference.

These, and other, design features add up to a highly reliable vacuum gauge with significant cost savings that are passed on to the user.

CVM211 Built-in Controller & Display

InstruTech's CVM211 *Stinger* module provides the necessary signal conditioning to turn the convection gauge into a complete vacuum measuring instrument.

The CVM211 *Stinger* module provides one log-linear or non-linear analog output and one setpoint relay. In addition, a built-in display provides the measured pressure values and provides a convenient user interface for setup and operation of the vacuum gauge.

Low-cost upgrade for thermocouple TC vacuum gauges

The CVM211 *Stinger* provides a wider measuring range than traditional thermocouple vacuum gauges - from 10⁻⁴ Torr to above atmosphere - so you can monitor your entire pump-down and vent cycle.

The CVM211 *Stinger* convection enhanced Pirani gauge is more accurate than a thermocouple gauge, especially at lower pressures. And depending on your gauge/readout configuration, the cost of a *Stinger* is about the same cost of a TC gauge system.

Also a direct drop-in replacement for Mini-Convectron[®]


The CVM211 *Stinger* can also directly replace the most basic Granville-Phillips[®] Mini-Convectron[®] modules, at significantly lower cost. The InstruTech *Stinger* provides equivalent or better performance throughout the range of 10⁻⁴ to 1000 Torr.

The 9-pin D-sub connector has the same pinouts and signals as the corresponding Mini-Convectrons[®]. The non-linear analog signal and setpoint relay are identical to their corresponding Mini-Convectron[®] functions. With *Stinger*'s performance, more robust design, longevity, smaller size, and lower cost, your process will only improve.

Guided by our vast experience and vacuum measurement know how, InstruTech sensors are specifically designed for optimum reliability and performance. Whether you're looking to reduce costs or improve your process, the CVM211 Stinger offers a cost-effective solution for your vacuum gauging needs.

Specifications

measurement range (signal)	1.0 x 10 ⁻⁴ to 1000 Torr / 1.3 x 10 ⁻⁴ to 1333 mbar / 1 x 10 ⁻² Pa to 133 kPa
accuracy - N ₂ (typical)	1.0 x 10 ⁻⁴ to 1.0 x 10 ⁻³ Torr; 0.1 mTorr resolution 1.0 x 10 ⁻³ to 400 Torr; ± 10% of reading 400 to 1,000 Torr; ±2.5% of reading
repeatability - (typical)	± 2% of reading
display	3 digit LED (3 digits from 999 Torr to 10.0 mTorr), (2 digit LED from 9.9 mTorr to 1.0 mTorr), (1 digit LED from 0.9 mTorr to 0.1 mTorr)
materials exposed to gases	gold-plated tungsten, 304 & 316 stainless steel, glass, nickel, Teflon®
internal volume	1.589 in ³ (26 cm ³)
internal surface area	9.25 in ² (59.7 cm ²)
weight	4.8 oz. (136 g)
housing (electronics)	molded plastic
operating temperature	0 to +40 °C
storage temperature	-40 to +70 °C
bakeout temperature	+70 °C max
humidity	0 to 95% relative humidity, non-condensing
mounting position	horizontal recommended
analog output	log-linear 1 to 8 Vdc, 1 V/decade, or non-linear analog S-curve 0.375 to 5.659 Vdc
input power	11 to 30 Vdc, 2 W, protected against power reversal, transients, and over-voltages
setpoint relay	one, single-pole double-throw relay (SPDT), 1 A at 30 Vdc resistive, or ac non-inductive
connector	9-pin D-sub male
RF/EMI protection	CE compliant
environmental	RoHS compliant



fitting	dimension A
1/8 in. NPT male - 1/2 in. tube	25.4mm (1.00")
NW16KF	33.0mm (1.30")
NW25KF	33.0mm (1.30")
NW40KF	33.0mm (1.30")
1 1/3 in. Mini-Conflat®	37.3mm (1.47")
2 3/4 in. Conflat®	37.3mm (1.47")
1/4 in. Cajon® 4VCR®	47.2mm (1.86")

Ordering Information

	Part Number	Part Number
	With Log-Linear analog output	With Non-Linear analog output
CVM211 Fittings / Flanges		
Combination 1/8 in. NPT male - 1/2 in. tube (use 1/8 in. NPT male or 1/2 in. O.D. O-ring compression)	CVM211GAL	CVM211GAA
NW16KF	CVM211GBL	CVM211GBA
NW25KF	CVM211GCL	CVM211GCA
NW40KF	CVM211GDL	CVM211GDA
1 1/3 in. Mini-CF / NW16CF Mini-Conflat®	CVM211GEL	CVM211GEA
2 3/4 in. CF / NW35CF Conflat®	CVM211GFL	CVM211GFA
1/4 in. Cajon® 4VCR® female	CVM211GGL	CVM211GGA
1/2 in. Cajon® 8VCR® female	CVM211GHL	CVM211GHA

Granville-Phillips® and Mini-Convectron® are registered trademarks of Brooks Automation, Inc. Chelmsford, MA. Conflat® is a registered trademark of Varian, Inc. / Agilent Technologies, Lexington, MA. Swagelok®, Cajon®, VCR® are registered trademarks of the Swagelok Company, Solon, OH. Teflon® is a registered trademark of E. I. du Pont de Nemours and Company, Wilmington, DE.



InstruTech®, Inc.
1475 S. Fordham St.
Longmont, CO 80503
USA

Phone +1-303-651-0551

Fax +1-303-678-1754

E-mail info@instrutechinc.com

Web www.instrutechinc.com